



110



111/112



113/114

Type			Configuration Size			Mounting Size						Structural Size			Gear Data (x=0.5)		External Gear Data		Internal Gear Data		Weight(KG)
Without Gear	External Gear	Internal Gear	D	d	H	D1	D2	r	dD1	dm1 M	L (Thread Length)	n1 (Grease Hole Qty)	H1	h	B	module	da	Z	da	Z	
									dD2	dm2 M											
110.25.500	111.25.500	113.25.500	602	398	75	566	434	20	18	M16	32	4	85	10	60	5	629	123	367	74	80
	112.25.500	114.25.500														6	628.8	102	368.4	62	
110.25.560	111.25.560	113.25.560	682	458	75	626	494	20	18	M16	32	4	85	10	60	5	689	135	427	86	90
	112.25.560	114.25.560														6	688.8	112	428.4	72	
110.25.630	111.25.630	113.25.630	732	528	75	696	564	24	18	M16	32	4	65	10	60	6	772.8	126	494.4	83	100
	112.25.630	114.25.630														8	774.4	94	491.2	62	
110.25.710	111.25.710	113.25.710	812	608	75	776	644	24	18	M16	32	4	65	10	60	6	850.8	139	572.4	96	110
	112.25.710	114.25.710														8	854.4	104	571.2	72	
110.28.800	111.28.800	113.28.800	922	678	82	878	722	30	22	M20	40	6	72	10	65	8	966.4	118	635.2	80	170
	112.28.800	114.28.800														10	988	94	634	64	
110.28.900	111.28.900	113.28.900	1022	778	82	978	822	30	22	M20	40	6	72	10	65	8	1062.4	130	739.2	93	190
	112.28.900	114.28.900														10	1068	104	734	74	
110.28.1000	111.28.1000	113.28.1000	1122	878	82	1078	922	36	22	M20	40	6	72	10	65	10	1168	116	824	83	210
	112.28.1000	114.28.1000														12	1185.6	96	820.8	69	
110.28.1120	111.28.1120	113.28.1120	1242	998	82	1198	1042	36	22	M20	40	6	72	10	65	10	1298	127	944	95	230
	112.28.1120	114.28.1120														12	1305.6	106	940.8	79	
110.32.1250	111.32.1250	113.32.1250	1390	1110	91	1337	1163	40	26	M24	48	5	81	10	75	12	1448.6	118	1048.8	88	350
	112.32.1250	114.32.1250														14	1453.2	101	1041.6	75	
110.32.1400	111.32.1400	113.32.1400	1540	1260	91	1487	1313	40	26	M24	48	5	81	10	75	12	1605.6	131	1192.8	100	400
	112.32.1400	114.32.1400														14	1607.2	112	1195.6	86	
110.32.1600	111.32.1600	113.32.1600	1740	1460	91	1687	1513	45	26	M24	48	5	81	10	75	14	1817.2	127	1391.6	100	440
	112.32.1600	114.32.1600														16	1820.8	111	1382.4	87	
110.32.1800	111.32.1800	113.32.1800	1940	1660	91	1887	1713	45	26	M24	48	5	81	10	75	14	2013.2	141	1573.6	113	500
	112.32.1800	114.32.1800														16	2012.8	123	1574.4	99	
110.40.2000	111.40.2000	113.40.2000	2178	1825	112	2110	1891	48	33	M30	60	8	100	12	90	16	2268.8	139	1734.4	109	900
	112.40.2000	114.40.2000														18	2264.4	123	1735.2	97	