



Slewing Bearing Without Gear

MODEL	DIMENSION				MOUNTING HOLE									N.W kg
					THOUGH HOLE (Type A)				SCREW HOLE (Type B, C, D)					
	D	d	H	h	D1	D2	ϕ	n	D1	D2	d1	L	n	
	mm				mm				mm					
QU315.20	408	222	60	10	370	260	17	10	370	260	M16	24	10	31
QU355.20	448	262	60	10	410	300	17	10	410	300	M16	24	10	33
QU400.20	493	307	60	10	455	345	17	12	455	345	M16	24	12	42
QU450.20	543	357	60	10	505	395	17	12	505	395	M16	24	12	47
QU500.20	593	407	60	10	555	445	17	14	555	545	M16	24	14	53

QU560.20	656	464	70	10	618	502	17	14	618	502	M16	30	14	72
QU630.20	726	534	70	10	688	572	17	16	688	572	M16	30	16	80
QU710.20	806	614	70	10	768	652	17	18	768	652	M16	30	18	91
QU800.20	896	704	70	10	858	742	17	20	858	742	M16	30	20	102
QU800.25	908	692	78	10	864	736	22	18	864	736	M20	36	18	130
QU900.25	1008	792	78	10	964	836	22	20	964	836	M20	36	20	146
QU1000.25	1108	892	78	10	1064	936	22	24	1064	936	M20	36	24	162
QU1000.32	1124	876	90	10	1074	926	24	24	1074	926	M22	40	24	212
QU1120.32	1244	996	90	10	1194	1046	24	28	1194	1046	M22	40	28	237
QU1250.32	1374	1126	90	10	1324	1176	24	32	1324	1176	M22	40	32	264
QU1400.32	1524	1276	90	10	1474	1326	24	36	1474	1326	M22	40	36	285
QU1250.40	1394	1108	102	12	1336	1164	26	32	1336	1164	M24	45	32	351
QU1400.40	1544	1258	102	12	1486	1314	26	36	1486	1314	M24	45	36	393
QU1600.40	1744	1458	102	12	1686	1514	26	40	1686	1514	M24	45	32	455
QU1800.40	1944	1658	102	12	1886	1714	26	44	1886	1714	M24	45	44	507
QU1600.50	1766	1434	124	12	1704	1496	30	40	1704	1496	M27	50	40	647
QU1800.50	1966	1634	124	12	1904	1696	30	44	1904	1696	M27	50	44	730
QU2000.50	2166	1834	124	12	2104	1896	30	48	2104	1896	M27	50	48	812
QU2240.50	2406	2074	124	12	2344	2136	30	54	2344	2136	M27	50	54	909
QU2500.50	2666	2334	124	12	2604	2396	30	60	2604	2396	M27	50	60	1015
QU2500.60	2696	2304	150	14	2626	2374	33	60	2626	2374	M30	56	60	1457